

■ SPECIFICATION

■ GEAR HEAD

Model		Ratio				Number of stages	Continuous torque [Nm]	Permissible load [N]		Efficiency [%]	Weight [Kg]
		(i : 1)	Coding	(i : 1)	Coding			Axial	Radial		
XPG	63	3	A1	–	–	1	15(*5)	800	800	90	0.7
		4	B1	–	–						
		7	C1	–	–						
		10	D1	–	–						
		14,5	E1	–	–						
		16,8	A2	50	E2	2	70	800	800	81	1.2
		29,4	B2	60,9	F2						
		35	C2	70	G2						
		42	D2	101,5	H2						
		70,6	A3	250	G3	3	100	800	800	73	1.8
		84	B3	304,5	H3						
		100	C3	362,5	I3						
		147	D3	426,3	J3						
		175	E3	507,5	K3						
210	F3	710,5	L3								

* : plastic planet gears

Model		Ratio				Number of stages	Continuous torque [Nm]	Permissible load [N]		Efficiency [%]	Weight [Kg]
		(i : 1)	Coding	(i : 1)	Coding			Axial	Radial		
XPG	75	4	A1	–	–	1	25	1000	1000	90	1.5
		5,5	B1	–	–						
		7	C1	–	–						
		10	D1	–	–						
		14,5	E1	–	–						
		16,8	A2	42	F2	2	120	1000	1000	81	2.5
		23,1	B2	50	G2						
		27,5	C2	60,9	H2						
		29,4	D2	70	I2						
		35	E2	101,5	J2	3	160	1000	1000	73	3.6
		70,6	A3	250	H3						
		84	B3	304,5	I3						
		100	C3	362,5	J3						
		115,5	D3	426,3	K3						
147	E3	507,5	L3								
175	F3	710,5	M3								
210	G3	–	–								